

FLECK® 2750

1-INCH CONTROL VALVE

IDEAL FOR RESIDENTIAL OR COMMERCIAL FILTER AND SOFTENER APPLICATIONS

FEATURES/BENEFITS

- | | |
|--|---|
| Lead-free brass valve body for superior strength and durability | Time-tested, hydraulically-balanced piston for service and regeneration |
| Continuous service flow rate of 26 GPM with a backwash of 25 GPM | Rugged-built electromechanical timer designed with heavy duty 3/8" wide plastic gears |
| Backwash capability accommodates softener tanks up to 30" and filter up to 21" in diameter | |
| Fully adjustable 3- or 5-cycle control for efficient and reliable water treatment system | |

OPTIONS

- | | |
|---|---|
| Filter or softener control valves | NXT- Network(e)10(vuses on-T)40(-)TJ ET EM |
| No hard water bypass piston | |
| Brine cam auxiliary switch | |
| Electromechanical timer auxiliary switch | |
| Hot water | |
| Electromechanical 7- or 12-day time clock, meter delayed, or meter immediate regeneration | |
| Manual lever operations | |

VALVE SPECIFICATIONS

Valve Material	Lead-free brass*
Inlet/Outlet	1" NPTM/BSPM
Cycles	3 or 5

FLOW RATES (50 PSI INLET) – VALVE ALONE

Continuous 15 psi drop	26 GPM
---------------------------	--------



FILTRATION & PROCESS

5730 NORTH GLEN PARK ROAD, MILWAUKEE, WI 53209

P: 262.238.4400 | WWW.PENTAIRAQUA.COM | CUSTOMER CARE: 800.279.9404 | tech-support@pentair.com | pentair.com

All Pentair trademarks and logos are owned by Pentair, Inc. or its affiliates. All other registered and unregistered trademarks and logos are the property of their respective owners. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice. Pentair is an equal opportunity employer.

40737 REV E JL14 © 2013 Pentair Residential Filtration, LLC. All Rights Reserved.