

FLECK® 3 00



FEATURES/BENEFITS

Lead-free brass valve body for superior strength and durability

Continuous service flow rate of 250 GPM with a backwash of 100 GPM

Backwash capability accommodates softener tanks up to 63" and filter up to 42" in diameter

Fully adjustable 3- or 5-cycle control for efficient and reliable water treatment system

Designed for single or multiple tank systems

Environmental protective cover for water resistance, corrosion resistance, and UV stability

Time-tested, hydraulically-balanced piston for service and regeneration

Rugged-built electromechanical timer designed with heavy duty 3/8" wide plastic gears

OPTIONS

Filter or softener control valves

Downflow co-current or upflow counter-current regeneration

No hard water bypass piston

Brine cam auxiliary switch

Electromechanical timer auxiliary switch

Treated water regeneration

VALVE SPECIFICATIONS

Valve Material	Lead-free brass*
Inlet/Outlet	3" NPTF/BSPF
Cycles	3 or 5

FLOW RATES (50 PSI INLET) – VALVE ALONE

Continuous	250 GPM (56.8 m
------------	-----------------



FILTRATION & PROCESS

5730 NORTH GLEN PARK ROAD, MILWAUKEE, WI 53209

P: 262.238.4400 | WWW.PENTAIRAQUA.COM | CUSTOMER CARE: 800.279.9404 | tech-support@pentair.com

© 2013 Pentair Water Filtration Systems, Inc. All rights reserved. Pentair, the Pentair logo, and other marks contained herein are trademarks of Pentair Water Filtration Systems, Inc. in the United States and other countries. Other marks contained herein are the property of their respective owners.